

REVERSIBLE TYPE SUCKER ROD SOCKET / OVERSHOT

The Titco Reversible Type Sucker Rod Socket is a combination slip socket for fishing sucker rods, polished rods, and sucker rod couplings (except surface-hardened couplings). Each socket is fitted with a reversible slip unit which has reverse wickers in each end. The large ID end of the slips will catch two sizes of couplings, while the opposite end will catch two sizes of rods. Multiple slips are available to catch worn boxes and pins; they will not catch rods.

Description			
Socket, Complete	2"		2½"
Outside Diameter	1 ²⁹ / ₃₂ "		2 ⁵ / ₁₆ "
COMPONENTS:		PRODUCT NUMBER:	
1 Bowl	552-521-000		554-522-200
2 Guide, Spring	552-705-000		552-705-100
3 Ring, Control	552-524-400		552-525-100
4 *Slips, Reversible			
1¼" to 1½" Couplings	552-520-500		
⅝" and ¾" Rods			
1½" to 1⅝" Couplings			552-521-600
¾" and ⅞" Rods			
5 Spring	552-521-200		552-522-300
6 Top (with ⅜" API pin)	552-520-900		552-522-000
7 *Slips, Multiple (worn boxes & pins)	552-520-600		552-521-800
8 *Slips, Polished Rod			
1⅝" and 1¾"	552-521-300		552-522-400
1¼" and 1½"			552-522-500
9 *Slips, Reversible			
1¼" to 1½" Couplings	552-520-530		
¾" to ⅞" Rods			
1½" to 1⅝" Couplings			552-521-500
⅝" to ¾" Rods			
1½" to 1⅝" Couplings			
1⅝" to 1"			552-521-700

* Slips come with control ring and guide.



TYPE B COMBINATION SLEEVE - TYPE SUCKER ROD SOCKET / OVERSHOT

The Trio Type B Sleeve-Type Sucker Rod Socket is used for fishing rod body breaks and sucker rod couplings. The socket has an upper bowl fitted with rod slips suitable for catching two sizes of rods, and a lower bowl fitted with a single end slip unit designed to engage and catch one size sucker rod coupling. All parts of the Type B socket are interchangeable with O'Bannon.

Description			
Socket, Complete	2"		2½"
Outside Diameter	1 ²⁹ / ₃₂ "		2 ¹¹ / ₃₂ "
COMONENTS:		PRODUCT NUMBER:	
1 Bowl, Lower	552-829-110		552-831-509
2 Bowl, Upper	552-829-310		552-831-609
3 Ring, Control	552-529-200		552-524-400
4 *Slips, Rod			
⅝" to ¾" Rods	552-827-800		
¾" and ⅞" Rods			552-830-100
5 Slips Unit, Single End Sleeve			
1⅝" Coupling	552-528-100		
1 ¹³ / ₁₆ " Coupling			552-531-409
6 Spring, Lower	552-821-200		552-822-300
7 Spring, Upper	552-829-400		552-831-700
8 Top (with ⅜" API pin)	552-828-900		552-822-000
9 *Slips, Rod			
¾" and ⅞" Rods	552-827-900		
⅞" to 1" Rods			552-830-200
10 Slip Unit, Single End Sleeve			
1⅜" Coupling	552-528-510		
1½" Coupling	552-528-500		
1 ⁷ / ₁₆ " Coupling	552-528-120		
1⅝" Coupling			552-831-903
2" Coupling			552-531-402

* Slips come with control ring and guide.



TRICO COMBINATION SLEEVE-TYPE SUCKER ROD SOCKET / OVERSHOT

The Trico Combination Sleeve-Type Sucker Rod Socket is used for fishing rod breaks and sucker rod couplings. The socket has an upper bowl fitted with rod slips suitable for catching two sizes of rods, and a lower bowl fitted with a single end slip unit designed to engage and catch one size sucker rod coupling.



Description			
Socket, Complete	2"		2½"
Outside Diameter	1 ²⁹ / ₃₂ "		2 ⁵ / ₁₆ "
COMPONENTS:		PRODUCT NUMBER:	
1 Bowl, Lower	552-529-000		552-531-500
2 Bowl, Upper	552-529-300		552-531-600
3 Guide, Spring, Lower	552-705-000		
4 Guide, Spring, Upper	552-705-400		552-705-100
5 Ring, Control	552-529-200		552-525-100
6 *Slips, Rod			
⅝" to ¾" Rods	552-527-800		
¾" and ⅞" Rods			552-530-100
7 Slips Unit, Single End Sleeve			
1⅝" Coupling	552-528-100		
1 ¹³ / ₁₆ " Coupling			552-531-400
8 Spring, Lower	552-521-200		552-522-300
9 Spring, Upper	552-529-400		552-531-700
10 Top (with ⅜" API pin)	552-528-900		552-522-000
11 Slips, Rod			
½" and ⅝" Rods	552-526-200		
⅝" to ¾" Rods			552-530-000
¾" and ⅞" Rods	552-527-900		
⅞" and 1" Rods			552-530-200
12 *Slip Unit, Single End Sleeve			
1⅞" Coupling	552-528-510		
1½" Coupling			552-531-410
1 ³ / ₁₆ " Coupling	552-528-120		
1⅝" Coupling			552-531-300
1 ¹³ / ₁₆ " Coupling			552-531-310

* Slips come with control ring and guide.

LITTLE GIANT SUCKER ROD SOCKET / OVERSHOT

The Trico Little Giant Sucker Rod is a combination slip socket used for fishing sucker rod breaks inside tubing. It can also be used inside a working barrel with corresponding size tubing and as a rod splicer for 2 inch tubing.



Description		
2" Socket, Complete		552-563-000
Outside Diameter		1 - 3/4"
COMPONENTS:		PRODUCT NUMBER
1 Bowl		552-527-000
2 Guide, Spring		552-705-400
3 Ring, Control		552-529-200
4 *Slips, Rod		
⅝" and ¾" Rods		552-527-800
5 Spring		552-529-400
6 Top (with ⅜" API pin)		552-528-800
7 *Slips, Rod		
½" and ⅝" Rods		552-526-200
¾" and ⅞" Rods		552-527-900
8 Top (with ⅜" API pin)		552-528-900

* Slips come with control ring and guide.

COMBINATION TAP & DIE SET

The Trico Combination Tap and Die Set is a handy on-the-spot thread chaser for use on all well servicing units. It allows the operator to repair rod threads and couplings in the field by setting correct factory thread pitch and contact area. The tool comes in three models and is made of the highest quality hardened steel to withstand severe service.



Description	Weight	Product Number
(Two Taps and Two Dies)		
1 ⅝" to ¾" API	7 lb	556-786-010
2 ¾" and ⅞" API	7 lb	556-786-020
3 ⅞" to 1" API	7 lb	556-786-030

P: 780-436-3400 | F: 780-436-3659 | Toll Free: 1-800-222-6448



Setting a
HIGHER STANDARD
NORTH AMERICAN MANUFACTURED WELL SERVICING TOOLS

IMPORTANT NOTES ABOUT THIS BROCHURE PRINTED JUNE 2026

All specifications and descriptions are accurate at the time of printing. Because continuous improvement is a goal at Topco Oilsite Products, we reserve the right to make changes in specifications at any time without notice and without obligation.



HEAVY LIFT ROD ELEVATOR CAPACITY 50,000 LB /25 TON

The Trico Heavy Lift Elevators is designed, tested, and documented to ensure compliance to API 8C specifications. The Trico Heavy Lift product is manufactured by Topco Oilsite Products following a strict Quality Control program for overhead lifting equipment. This elevator is engineered to eliminate sharp edges or protrusions which could cause accidents or malfunctions during operation.

Description	Weight	Product Number
Elevator, Without Plates & Screws	34.5 lb	553-575-500
COMPONENTS: KIT QUANTITY:		
1 Link	4	553-548-500
2 Pin for Lever, Rear	4	553-548-900
3 Spring	4	553-549-010
4 Lever, Release, Rear	4	553-551-000
5 Pin, Link	8	553-551-400
6 Latch, Release, Front	4	553-551-500
7 Spring Retaining Rings	4	553-551-800
8 Pin, Drive, Latch	4	553-766-100
ACCESSORIES:		
9 Screw (Allen Head), Plate Plates:		553-554-000A
5/8" - 3/4" Rods		553-550-000
3/4" - 7/8" Rods		553-550-200
1" Rod		553-550-700
1 1/8" Rod		553-550-750
1 1/4" Rod		553-550-800

OPTIONAL ELEVATORS AVAILABLE:

1 1/8" Solid Body Steel Rod	553-575-100
1 1/4" Steel Rod Plate Type	553-575-200
1 1/4" Polish Rod Solid Body	553-575-300
1 1/2" Polish Rod Solid Body	553-575-800
1 1/2" Polish Rod Solid Body (65,000 lb/32.5 Ton)	553-574-365
Kit Repair (For Two Elevators)	553-579-600
Kit Repair for Polish Rods (For One Elevator)	553-579-300

* Repair Kits consist of parts for two elevators (latches, levers, pins, links, latch springs, and screws where applicable).



HEAVY LIFT PLATE STYLE (WITH 1" ROD)

HEAVY LIFT POLISH ROD STYLE (WITH SUPPORT BRACE)

- SPECIAL ORDER 65,000 lb Polish Rod Elevators available
- TEMPERATURE RATED for -46 °C
- LOAD TESTED at 1.5x

ROD SPINNER CAPACITY 50,000 LB /25 TON

The Topco Rod Spinner is engineered as a safety device to handle the release of sucker rod energy when a Progressive Cavity Pump is unseated. It reduces the risk of personal injury as well as preventing surface equipment from being damaged. It has been designed for efficiency to quick connect to a Rod Clevis on most energy service rigs, flushbys and rod rigs. It has a load rating of 50,000 lb allowing the Rod Spinner to be used to pull on both sucker and polish rods.



Description	Weight	Product Number
1" PE Rod Spinner	30 lb	557-501-600
COMPONENTS:		
1 Grease Cap Kit		554-542-500
2 Nut		554-542-901
3 Bearing		554-543-400
4 Screw, Grease Cap		554-542-600

Patent Numbers
6.253.844 | USA
2.282.822 | Canada

TUBING SPINNER CAPACITY 50,000 LB /25 TON

The Topco Tubing spinner is designed to create a safe environment when unseating downhole pumps and progressive cavity pumps which might have a torque buildup. This will cause the Sucker Rods to unscrew or relieve the torque violently. The Topco Tubing Spinner reduces the chance of injury and equipment damage by safely relieving the kinetic energy in the rod/pump assemblies.

Description	Product Number
2 7/8" Tubing Spinner	558-501-500
3 1/2" Tubing Spinner	558-501-600



HEAVY LIFT SHORT ROD HOOK CAPACITY 50,000 LB /25 TON

Trico Rod Hooks are designed for operating speed and safety. They feature a special snap-in latch mechanism which permits the elevator bail to enter the hook opening without the latch being released by the operator. When the bail is engaged the hook spring automatically forces the latch to a locked position, holding the elevator secure until released. The latch spring is enclosed in a housing to prevent fouling. Trico Rod Hooks are made of high-grade steel, heat treated for long life.

Description	Weight	Product Number
Short Hook, Complete	42 lb	554-578-600
COMPONENTS:		
1 Bearings, Roller, Heavy Duty		554-543-400
2 Grease Cap Kit		554-542-500
3 Spring Housing		554-544-800
4 Latch		554-544-400
5 Lever		554-544-200
6 Nut & Pin		554-542-901
7 Pin, Latch		554-543-105
8 Pin, Lever		554-543-100
9 Set Screw		554-542-700
10 Screw, Grease Cap		554-542-600
11 Spring, Latch		554-544-700
ACCESSORIES:		
Kit, Repair		554-579-000

* Repair Kits consist of Latch, Lever, Latch Pin, Lever Pin, Spring and Spring Housing.



- TEMPERATURE RATED for -46 °C
- LOAD TESTED at 1.5x

SUPER LIFT LONG ROD HOOK CAPACITY 50,000 LB /25 TON

The Trico Snap-In Spring Lift Rod Hook has an extra long shank containing a heavy coil spring which supports the section of rods being pulled. The spring protects the rod threads while the rods are being removed from the tubing. The additional weight of this hook assists in unspooling the line from the pulling unit.



- TEMPERATURE RATED for -46 °C
- LOAD TESTED at 1.5x

Description	Weight	Product Number
Long Hook, Complete	65 lb	554-578-950
COMPONENTS:		
1 Bearings, Roller, Heavy Duty		554-543-400
2 Grease Cap Kit		554-542-500
3 Spring Housing		554-544-800
4 Latch		554-544-400
5 Lever		554-544-200
6 Nut & Pins		554-542-902
7 Pin, Latch		554-543-105
8 Pin, Lever		554-543-100
9 Set Screw		554-542-700
10 Screw, Grease Cap		554-542-600
11 Spring, Latch		554-544-700
12 Spring, Coil		554-543-700
ACCESSORIES:		
Kit, Repair		554-579-000

* Repair Kits consist of Latch, Lever, Latch Pin, Lever Pin, Spring and Spring Housing.

PARAFFIN KNIFE

The Trico Paraffin knife features a field proven paraffin removing design. It is a rugged, flexible tool available in two sizes.

Description	Weight	Product Number
Knife, Paraffin, Complete		
2" (with 3/4" API pin)	3 3/4 lb	556-793-000
2 1/2" (with 3/4" API pin)	4 lb	556-792-700
ACCESSORIES:		
Disk, Scraper, Paraffin Knife	1/4 lb	556-792-800
2" (2 3/8" tubing)		
Disk, Scraper, Paraffin Knife	1/4 lb	556-792-900
2" (2 3/8" tubing)		



ULTRA MAX SHORT ROD HOOK CAPACITY 75,000 LB /37.5 TON

Trico is proud to introduce the Ultra Max series Rod Hooks. The Ultra Max boasts industry leading load ratings and is engineered with safety in mind. Ultra Max Rod Hooks feature a newly designed locking latch mechanism for utmost safety during operation. This new latch system ensures that the latch will not open unless the lever is manually engaged and that the load is securely held in the hook until the latch is released by the operator. Trico rod hooks are made of high-grade steel and heat treated for toughness.

Description	Weight	Product Number	ACCESSORIES:
Short Rod Hook, Complete	74 lb	554-778-600	Kit, Repair 554-778-000
COMPONENTS:			
1 Ultra Max Nut w/ Pin		554-700-902	
2 Grease Cap Kit		554-542-500	
3 Lever Pin		554-700-150	
4 Latch Pin		554-700-175	
5 Ultra Max Latch		554-744-400	
6 Ultra Max Lever		554-700-200	
7 Bearing		554-743-400	
8 Latch Spring		554-700-700	

* Repair Kits consist of Latch, Lever, Latch Pin, Lever Pin, and Lever Spring.



- TEMPERATURE RATED for -46 °C
- LOAD TESTED at 1.5x

ULTRA LONG ROD HOOK CAPACITY 75,000 LB /37.5 TON

The Ultra Max Long Hook is equipped with the same safety features and load capacity as the Ultra Max Short Hook. The Long Hook has an extended shank containing a heavy coil spring that supports the rod section. This spring design protects the threads by reducing shock load on the rod coupling while removing them from the tubing.

Description	Weight	Product Number	ACCESSORIES:
Long Rod Hook, Complete	91 lb	554-778-800	Kit, Repair 554-778-000
COMPONENTS:			
1 Ultra Max Nut w/ Pin		554-700-902	
2 Grease Cap Kit		554-542-500	
3 Ultra Max Shaft Spring		554-743-700	
4 Lever Pin		554-700-150	
5 Latch Pin		554-700-175	
6 Ultra Max Latch		554-744-400	
7 Ultra Max Lever		554-700-200	
8 Bearing		554-743-400	
9 Latch Spring		554-700-700	

* Repair Kits consist of Latch, Lever, Latch Pin, Lever Pin, and Lever Spring.



- TEMPERATURE RATED for -46 °C
- LOAD TESTED at 1.5x

ROD BUSTER SUCKER ROD WRENCH

The Trico snap-action Rod Buster Sucker Rod Wrench is made of high-grade alloy steel, hardened to resist wear. This lightweight (6 lb), rugged tool is excellent for manual makeup and breakout of sucker rod joints. It features a counterbalanced grip to reduce fatigue. The cross-section of the handle is oval which provides a natural resistance to the wrench spinning when gripped. The head is spring-loaded and a hardened steel bushing is provided between the wrench head and handle.



19" Handle

Description	Product Number
Sucker Rod Wrench Assembly Part	Wrench Head Part #2
1 555-560-000	555-560-100
2 555-560-050	555-560-200
3 555-560-065EL	555-560-250EL
4 555-560-075	555-560-275
5 555-560-175	555-560-285
COMPONENTS:	
6 Kit Repair (consists of 1 spring, 1 plunger, 1 rivet, and 1 bushing)	555-560-950